




EPIQ 3RE Downlight

Features

- Excellent color rendering (90+ CRI)
- 3000K color temperature
- Up to 700 lumen output
- Consumes only 8 watts
- Swivel option available for greater flexibility
- CLIQ square trims instantly transform the look
- Dimmable with most TRIAC, CL, or ELV dimmers
- cETLus Listed for damp locations
- 35,000 hours rated life
- ENERGY STAR certified

Available Finishes



Dimming Options

- ELV (5-100%)
- TRIAC (5-100%)

Listing / Ratings



CLIQ 3 Trim



For use with E3-RE only; Excludes E3S-RE

Technical Information

Series	E3-RE / E3S-RE
Input Voltage	120V AC, 60Hz
CCT	3000K
CRI	90+
Wattage	8W
Lumens	Up to 700Lm
Beam Angle	90°
Dimmable	5-100%
Mounting	Recessed mount* (3-3/8" cut-out)
Rating	cETLus Listed; Suitable for damp locations
Rated Life	35,000 hrs

*Recessed housing is type NON-IC

Ordering Information

E3-RE-30-WH	3" White Smooth / 3000K / 700Lm
E3-RE-30-NK	3" Nickel Smooth / 3000K / 550Lm
E3-RE-30-DB	3" Dark Bronze Smooth / 3000K / 460Lm
E3S-RE-30-NK	3" Nickel Gimbal / 3000K / 550Lm
E3S-RE-30-DB	3" Dark Bronze Gimbal / 3000K / 480Lm
Q3-WH	3" Cliq Trim / White Smooth
Q3-NK	3" Cliq Trim / Nickel Smooth
Q3-DB	3" Cliq Trim / Dark Bronze Smooth

