




Features

- Class 2, 16W 350mA constant current driver
- Compatible with ENCL-11 power supply enclosure
- Controls 3-11 LEDs in non-dimming applications
- Class II double insulation barrier for surge protection (no ground connection)
- Auto-reset protection for short circuit and over-voltage
- cURus Recognized (dry and damp locations)
- RoHs Compliant

Compatible Power Supply Enclosure (ENCL-11)



Listing / Ratings



350mA 16W Driver

The LED-DR16-350 features universal 94-264V AC power input with high reliability and Class 2 rating. This constant current driver powers 3-11 350mA LEDs in non-dimming applications. Its compact, sturdy design and fully isolated Class II design, allow it to cool by free air convection and operate at case temperatures from -22°F to 158°F in dry and damp locations.

Technical Information

| | |
|-----------------|---|
| Series | LED-DR 350mA |
| Max Load | 16W |
| Minimum Load | 3.75W |
| Input Voltage | 90-264V AC, 50/60Hz |
| Output Current | 350mA |
| Dimmable | N/A |
| Efficiency | 84% |
| Input Wire | 5" 18AWG |
| Output Wire | 5" 20AWG |
| Operating Temp. | -22°F - 158°F (-30°C - 70°C) |
| Rating | cURus Recognized (dry and damp locations) |
| Dimensions | 3-1/2"L x 1-5/8"W x 1-3/16"H |

Ordering Information

| | |
|---------------------|--------------------|
| LED-DR16-350 | 350mA - 16W driver |
|---------------------|--------------------|