




## Features

- Class 2, 18W 350mA constant current driver
- Compatible with ENCL-11 power supply enclosure
- Controls 3-12 LEDs in dimming applications (dimming consumes 3W internally)
- cURus Recognized (dry and damp locations)
- RoHs Compliant

## Dimming Options

- CL
- ELV

Compatible Power Supply Enclosure (ENCL-11)



## Listing / Ratings



## 350mA 18W Driver

The LED-DR18-350D2 features universal 120-277V AC power input with high reliability and Class 2 rating. This constant current driver powers 3-12 350mA LEDs in dimming applications. Its compact, sturdy design and fully isolated Class II design, allow it to cool by free air convection and operate at case temperatures from -22°F to 158°F in dry and damp locations. Convenient mounting tabs allow quick anchoring as needed.

## Technical Information

Series	350mA
Max Load	18W (non dimming); 15W (dimming)
Minimum Load	3W (non-dimming); 3.75W (dimming)
Input Voltage	120-277V AC, 50/60Hz
Output Current	350mA
Power Factor	0.96
Dimmable	ELV / CL (35 %)
Efficiency	85
Input Wire	8" 18AWG
Output Wire	8" 18AWG
Operating Temp.	-13°F - 122°F (-25°C - 50°C)
Rating	cURus Recognized (dry and damp locations)
Dimensions	6"L x 1-1/8"W x 1-3/16"H

## Ordering Information

<b>LED-DR18-350D2</b>	350mA - 18W Dimming driver
-----------------------	----------------------------