



PROJECT:

TYPE:

LOCATION:

CAT:



Description

Trulux back-lit touch wall control for single color light control; 1-4 operation with 1-3 scene control.

Features

- Touch for On/Off control
- Swipe for full range dimming (1-100%)
- Smooth glass faceplate with illuminated controls
- Radio frequency (RF) signal range up to 65 feet
- Control multiple receivers in multiple zones (1-4)
- 3 customizable scenes
- Requires 12-24V DC input
- Requires Trulux RF receiver for operation (sold separately)

Mounting

Flush mount to wall or flat surface (1-3/4" x 2-5/8" cut-out)

Applications

Dimming, zone, and scene control for single color light

Warranty


3 years

Technical Information



Voltage	12-24V DC
Power Consumption	200mA
Frequency	916.5Hz RF wireless
Operating Temperature	0° - 40°C
Relative Humidity	8% - 80%
Rating	FCC Compliant, RoHS Compliant, dry location

Dimensions



Required Receivers

Part Number	Description	Application	Input	Current	Output	Listing	Dimensions
REC-5A-4Z	Trulux RF Constant Voltage Receiver	Dry location	12-36V DC	4x5A	4x(60-180)W	RoHS	7-1/16" x 1-13/16" x 6-23/32" (178.9mm x 45.5mm x 18.6mm)

Controller can be powered from secondary side of 12-24V DC driver being used to power the Trulux receiver/Trulux tape light. See 'Trulux Control Options' for selected tape light for more information.

Ordering Information

**Trulux Back-lit
Touch Wall
Control**



SRF-4Z-3P includes:

(1) Trulux Back-lit Touch Wall Control (requires 12-24V DC input & Trulux receiver)

Example Part # **SRF-4Z-3P**

