



LAMP SPECIFICATIONS

12V Lamps	Item #	Watts	Lumens	Efficacy (LPW)	Color Temp (Kelvin)	Average Life (hours)	Base	MOL (inches)
	CLED-12VAC-30	.2	-	-	varies by color	60,000	Round Wedge	19/32
	013-0001	75	2,500	33.3	3000	3,000	G6	1-3/4
	AL10BX	10	140	14.0	2800	10,000	G4	1-1/8
	ALPX20B	20	235	11.8	2800	10,000	G4	1-1/16
	AL20B	20	145	7.2	2800	2,000	G4	1-3/16
	FSL-5-12	5	33	6.6	2550	20,000	Festoon	1-11/16
	FSL-10-12	10	83	8.3	2650	20,000	Festoon	1-11/16
	FSL-5F-12	5	33	6.6	2550	15,000	Festoon	1-11/16
	FSL-10F-12	10	83	8.3	2650	15,000	Festoon	1-11/16
	MR-11-12-20	20	220	11.0	3000	2,000	G4	1-11/16
	FSL-WW-12	.82	19	23.2	2700	60,000	Festoon	1-11/16
24V Lamps	Item #	Watts	Lumens	Efficacy (LPW)	Color Temp (Kelvin)	Average Life (hours)	Base	MOL (inches)
	CLED-24VAC-30	.2	-	-	varies by color	60,000	Round Wedge	19/32
	FSL-5-24	5	33	6.6	2,550	20,000	Festoon	1-11/16
	FSL-10-24	10	83	8.3	2,650	20,000	Festoon	1-11/16
	FSL-5F-24	5	33	6.6	2,550	15,000	Festoon	1-11/16
	FSL-10F-24	10v	83	8.3	2,650	15,000	Festoon	1-11/16
	MR-11-24-20	20	230	11.5	3,000	2,200	G4	1-5/16
	FSL-WW-24	.82	19	23.2	2700	60,000	Festoon	1-11/16

120V Lamps	Item #	Watts	Lumens	Efficacy (LPW)	Color Temp (Kelvin)	Average Life (hours)	Base	MOL (inches)
	043T-F06/30	6	310	51.7	3000	10,000	T2 Axial	8-9/16
	043T-F08/30	8	500	62.5	3000	10,000	T2 Axial	12-5/8
	043T-F13/30	13	860	66.2	3000	10,000	T2 Axial	20-9/16
	043T-F18/30	18	1120	62.2	3000	10,000	T2 Axial	26-3/4
	043T-F24/30	24	1240	51.7	3000	10,000	T2 Axial	30-3/4
	LXCP-10BP	20	90	4.5	2800	8,000	G8	1-3/8
	043X-20BP	20	165	8.2	2800	8,000	G8	1-3/4
	LHC35B-BP	35	390	11.1	2900	2,500	G8	1-3/4
	LVPX20BP	20	90	4.5	3100	8,000	G8	1-3/8
	ALLVP20B	20	145	7.2	2800	2,500	G8	1-3/8
	ALFL8B	8	440	55.0	3100	8,000	T4 Bi-pin	12-15/16
	ALFL16B	16	960	60	3100	8000	T4 Bi-pin	18-11/16
	ALFL16B-64	16	1040	65.0	6400	8,000	T4 Bi-pin	18-11/16